

Plastuc Tipo A

Filling plaster in paste for interior use.



Mod. 51 Rev 64

Last update 30/10/2019

CHARACTERISTICS:

PLASTUC TIPO A is a smoothing plaster composed of vinyl versatate resins in water emulsion, mineral fillers, additives and binders to improve workability of the product.

PLASTUC TIPO A is a thick white paste with high filling power, a good degree of fineness, which does not shrink, dries quickly and it is easy to sand. Once applied it provides smooth and compact surfaces, with good surface hardness. It has good permeability to water vapour and is ideal, after adequate preparation, for the application of water-based or alkyd paints.

PLASTUC TIPO A is free of ammonia, does not contain any harmful substance, is odourless and non-flammable.

USE:

Thanks to its characteristics **PLASTUC TIPO A** is ideal for filling any type of small hole and crack, or for levelling and smoothing large surfaces of interior walls and ceilings both on residential and industrial buildings. It is therefore especially suitable on cement plaster, precast concrete, plasterboard, gypsum, scagliola, old paints in good condition and well-adherent, wood and its derivatives, provided that the substrate is solid, dry and absorbent.

PLASTUC TIPO A is also the ideal basecoat for **STUCCO DI VENEZIA** on rough and/or non-uniform surfaces.

PREPARATION AND APPLICATION:

Apply on a clean and dry substrate, completely free from dust. Remove any non-adherent plaster or old paint. Treat in advance any presence of mould and other contaminants with **MUROSANO RISANANTE**. On chalky plaster, old paint, stained surfaces, apply a first coat of **PRIMER A**. After about 2 - 3 hours apply **PLASTUC TIPO A** with a small steel spatula to fill holes and cracks, or by steel trowel to level and smooth large surfaces. The product is ready to use and is generally applied in two or more layers, at a short interval between one coat and the other. Just wait enough time for the previous layer to set. After application of the last coat, once the surface is perfectly dry, it is possible to make it even smoother by sanding it with fine sandpaper. Before applying any paint or coating, consolidate the surface by applying one coat of **PRIMER A**.

IMPORTANT NOTES:

- Before application, make sure that the substrate is perfectly dry and cured and perfectly anchored. The surface must be free from dust, dirt, grease, moulds, fungi, bacteria, efflorescence or anything else likely to prevent good adhesion and a successful result.
- Protect containers from frost (minimum + 5°C).
- Store in a cool, dry place away from sunlight.
- Use the product at room and surface temperature between + 8°C and + 35°C and with relative humidity below 75%.
- Avoid drying at room or surface temperatures below + 5°C
- Do not apply when rain is imminent, in full sunlight, when it is very windy or with persistent fogs.
- Wash all tools with water immediately after use.

TECHNICAL DATA:

Drying time at 25°C (1 mm thickness)	Touch dry 1 hour In depth 12 hours Overpainting 8 – 12 hours
Volume solids at 105°C	76%
pH	8.5 ± 1
Consumption rate	0.25 – 0.50 kg/m ² per applied layer
Product type	Water-based
Storage	12 months in sealed original packages in proper storing conditions
Colour	white
Packages	20 kg - 5 kg - 1 kg

Plastuc Tipo A

Filling plaster in paste for interior use.



Mod. 51 Rev 64

Last update 30/10/2019

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Please refer to the relevant Safety Data Sheet.