

Heavy Metal Rev 2.0

Decorative water-based finish with brushed metal effect. Mould resistant formula



Mod. 51 Rev 64

Date of update 30/10/2019

CHARACTERISTICS:

Decorative water-based finish with styrene-acrylic resins and bright metallic pigments. **HEAVY METAL** gives the surface to which it is applied a "brushed metal" effect to create a special atmosphere in interior. Thanks to its high filling power, **HEAVY METAL** can hide surface unevenness and defects, and is highly resistant to wear. **HEAVY METAL** also has good elasticity and adherence, it is washable, non-flammable and water-based, and therefore safe for the environment and the human-being. With mould resistant formula.

HEAVY METAL is available in 3 bases which can be coloured with **Colorplus**® tinting system

- **ORO** (Gold)
- **ORO BIANCO** (White Gold)
- **BRONZO** (Bronze)

And in the stand-alone colour **FOGLIA ORO** (GOLD LEAF), ready to use.

USE:

Finish for the decoration of interior walls and ceilings made of bricks, plasterwork, concrete, mortar, plaster and similar, plasterboard, old paint, wood, hardboard, terracotta, ceramic tiles, paper, cardboard, etc. **HEAVY METAL** is particularly suitable for decorating public spaces such as cafés, bars, clubs, restaurants and hotel, and private homes designed according to the last trends in interior decoration.

PREPARATION AND APPLICATION:

Surfaces must be as free as possible from defects. Scrape, brush and remove old paintwork or loose plasterwork. Ensure that the surface is solid, dry and clean. Seal any infiltrations of damp beforehand. Fill any cracks and holes and smooth rough surfaces. Apply a first coat of **SMARTCOAT EXTRATHIN GRAIN 0.1mm** by brush or roller. Apply a first coat of **HEAVY METAL** with a spalter brush or paint brush. Apply product with crossed strokes, making sure to apply it evenly on the full surface. After 2-3 hours apply a second coat of **HEAVY METAL** by brush, to ensure uniform distribution of product.

IMPORTANT NOTES:

- Carefully mix the product before use.
- Before application, ensure that the surface is perfectly dry and hardened, and that it has good adherence to the supporting ground. It must be clean and free from oil, grease, mould, fungus, bacteria, efflorescence or any other defect that could impair adherence or successful results.
- Protect containers from freezing (minimum + 5° C).
- Store in a cool, dry place and do not expose to direct sunlight.
- Use product at a temperature of the work environment and treated surface between 8°C and 35°C. Relative humidity must not exceed 75%.
- Do not allow drying to take place with temperature of the work environment and treated surface below +5°C.
- Ensure that a sufficient quantity of the same batch of paint is available to complete the entire job, or at least to complete whole sections that will not reveal differences in shade.
- Wash all equipment with water immediately after use.

Heavy Metal Rev 2.0

Decorative water-based finish with brushed metal effect. Mould resistant formula



Mod. 51 Rev 64

Date of update 30/10/2019

TECHNICAL DATA:

Coverage	7-10 m ² /l = 0.10-0.14 l/m ² according to application method.
Packages	2.5 l – 1 l
Storage	At least 12 months in perfectly sealed packages away from cold.
Colours	Collection Heavy Metal
Bases	ORO ORO BIANCO BRONZO FOGLIA ORO (stand alone colour)

Emission limits of Volatile Organic Compounds (VOC) according to directive 2004/42/CE:

Classification: A/ I) "decorative effect coatings";

Limit Phase II (from 01/01/ 2010): 200 g/l

VOC: 100 g/l (max)

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Please refer to the relevant Safety Data Sheet.