

# Antica Patinatura

Acrylic paste for artistic finish effects for interior use.  
Mould resistant formula



Mod. 51 Rev 64

Last update 05/02/2020

## CHARACTERISTICS:

**ANTICA PATINATURA** is an acrylic decorative paste, protective and water-repellent, used to create artistic decorative effects on indoor surfaces. Formulated with acrylic resins and iridescent pigments, it consists of a thick paste that once spread out on a surface it appears as a smooth silky finish, that protects from grease and dirt. When applied on textured surfaces it increases the depth of the finish effect. Mould resistant formula

## USES:

Particularly suitable as a protective and decorative paste for polished plaster, Venetian plaster and textured coatings. It can also be applied on acrylic paints as long as they are absorbent, not flaking and well adherent to the substrate. **ANTICA PATINATURA** shows its best results when applied on **COCCIO ANTICO TRAVERTINO, RILIEVI, MARMO DI VENEZIA, INTONANTICO 0.8 mm, RASATO FINE, RASATO TRAVERTINO, ACCADEMIA STRUCTUR, MURO ANTICO, CREATIVO MICROCEMENTO.**

## PREPARATION AND APPLICATION:

On a perfectly dry substrate, apply a very thin coat of **ANTICA PATINATURA** by stainless-steel or PVC trowel, sponge or fur glove, according to the effect desired. Press well with the tool on the surface in order to ensure a smooth and uniform application.

The product can be applied with circular movements or crossed strokes, depending on the desired decorative effect; by overlapping different or contrasting colours and nuances it is possible to create endless decorative effects depending only on the decorator's imagination.

## IMPORTANT NOTES:

- Before applying, make sure that the surface is perfectly dry and cured and perfectly anchored to the substrate, that it is not dirty, greasy, contaminated by moulds, fungi, bacteria, effloresce or anything else likely to prevent good adhesion and a successful result.
- Protect packaging from frost (minimum + 5°C)
- Store in a cool, dry place away from sunlight.
- Use the product at room and support temperature between + 8°C and + 35°C and with relative humidity not above 75%
- Avoid drying at room or support temperatures below + 5°C
- Wash tools with water after use.
- Do not expose the treated surfaces to washing with water as the product will become soluble and be washed away

## TECHNICAL DATA:

Dilution	Ready to use
Appearance of dry film	Silky pearlescent
Consumption	0.050 – 0.070 l/m <sup>2</sup>
Density (UNI EN ISO 2811-1:2003)	1.00 ± 0.05 kg/l
pH	~ 8,5 ± 1
Drying time at 20°C	Dust dry 2 hours, in depth 12-24 hours.
Bases	Gold, Copper and Silver (colourable)
Packages	2.5 l - 1 l
Colours	Collections <i>Velature</i> and <i>Rilievi</i> .

Emission limits of Volatile Organic Compounds (VOC) according to directive 2004/42/CE:

l) decorative effect coatings:

Limit VOC value in g/l: since 01.01.2010 = 200 g/l

Max VOC value in the product: 100 g/l.

# Antica Patinatura

Acrylic paste for artistic finish effects for interior use.  
Mould resistant formula



Mod. 51 Rev 64

Last update 05/02/2020

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Please refer to the relevant Safety Data Sheet.