

Veli D' Oriente Rev 1.1



Decorative pearlescent finish, with shimmering reflections recalling the play of light of precious fabric, that create an exotic atmosphere.

Mod. 51 Rev 64

Date of update 11/12/2019

A journey to discover the perfumes of far and exotic oriental places along the trail of Marco Polo. **VELI D'ORIENTE** is a decorative finish that offers the silkiness and reflections of precious fabrics and the play of lights and colours that give interior walls a sense of exotic enchantment. Mould resistant formula.

CHARACTERISTICS:

VELI D'ORIENTE is composed by synthetic and natural oils and resins, extrathin inert fillers and additives to give excellent workability. **VELI D'ORIENTE** has good elasticity and adherence, is non-flammable, is washable, water-based and therefore harmless for people and the environment.

USE:

VELI D'ORIENTE is the ideal solution for interiors, where a smooth and shiny finish of great value combined with good resistance and washability is wanted. Suitable for hotel halls, banks, offices, shops and particularly elegant interiors. Can be applied to a wide range of surfaces, including plasterwork, plaster, plasterboard, wooden furniture and panels, painted walls and smoothing compounds, as long as these surfaces are sound, clean and free from damp and efflorescence.

PREPARATION AND APPLICATION:

Clean the surfaces that are going to be painted, removing any loose and flaky material. Apply one coat of **PRIMER A**, fully saturating the surface. On rough and uneven surfaces apply several coats of **PLASTUC TIPO A**, smoothing with a steel spatula until a perfectly flat and smooth surface is obtained. When the surface is completely dry, apply one coat of **SMARTCOAT EXTRATHIN 0.1 mm** with a short bristle roller. When the undercoat is completely dry, apply the first coat (diluted 50% with water) of **VELI D'ORIENTE** with a short bristle roller. Apply the 2nd coat of **VELI D'ORIENTE** on the surface with a steel trowel. When the product is drying press it with low pressure in order to obtain the characteristic colour variations given by the substances contained in the product.

IMPORTANT NOTES:

- Before application, ensure that the surface is perfectly dry and cured, and well adherent to the substrate. Surface must be clean and free from oil, grease, mould, fungus, bacteria, efflorescence or any other defect that could impair adherence or successful results.
- Protect containers from freezing (minimum + 5° C).
- Store in a cool, dry place; do not expose to direct sunlight.
- Use product at a temperature of the work environment and treated surface between 8°C and 35°C. Relative humidity must not exceed 75%.
- Do not allow drying to take place with temperature of the work environment and treated surface below 5°C.
- Scaffolding should be erected in a way that allows work to be continued uninterrupted until a natural boundary of the building is reached, to avoid seams, overlaps and differences in colour.
- Ensure that a sufficient quantity of the same batch of paint is available to complete the entire job, or at least to complete whole sections that will not reveal differences in shade.
- Given the many different factors that may affect the outcome of application, in any case of doubt contact our Technical Service.

Veli D' Oriente Rev 1.1

Decorative pearlescent finish, with shimmering reflections recalling the play of light of precious fabric, that create an exotic atmosphere.



Mod. 51 Rev 64

Date of update 11/12/2019

TECHNICAL DATA:

Drying time at 20°C	touch dry 1 hour, in depth 24 hours
Dilution	1 st coat: 50% with water 2 nd coat: non-diluted
Consumption rate	1 st coat: 0.040 – 0.050 l/m ² = 20 - 25 m ² /l 2 nd coat: 0.100 – 0.120 l/m ² = 8 - 10 m ² /l
Specific weight	0.95 ± 0.05 kg/l
Dry residue at 105°C	51% ± 1%
pH	~8
Storage time	24 months
Appearance of dry film	Smooth shiny trowelled effect.
Bases	Gold and Silver
Colours	"Veli d'Oriente" Colour collection
Packages	2.5 l - 1 l

Emission limits of Volatile Organic Compounds (VOC) according to directive 2004/42/CE:

Classification: A/ I) "decorative effect coatings";

Limit Phase II (from 01/01/ 2010): 200 g/l

VOC: 110 g/l (max).

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Please refer to the relevant Safety Data Sheet.