

Cera per Stucco di Venezia rev 2.0



Protective wax with a high-gloss effect for Stuccoes and Venetian plaster.

Mod. 51 Rev 64

Date of update 11/12/2019

CHARACTERISTICS:

CERA PER STUCCO DI VENEZIA is an emulsion of bee waxes and synthetic resins. Once applied, it gives the surface a high-gloss effect, smooth to the touch, that improves resistance to water, dirt and oil. The product does not yellow overtime.

USE:

CERA PER STUCCO DI VENEZIA is ideal for the protection of decorative stuccoes and Venetian plaster, marmorinos and polished plaster. Suitable to improve water-resistance of the surface, conferring it a glossy effect at the same time.

Due to its composition, the product will modify system's vapour permeability when applied on mineral products.

PREPARATION AND APPLICATION:

Apply **CERA PER STUCCO DI VENEZIA** on a perfectly dry substrate, spreading the product with the specific stainless-steel trowel for **MARMO DI VENEZIA** (with rounded edges and blade), in order to avoid accumulations, and then polish the surface with a woollen cloth or lambswool pad. The treated surface will acquire water-repellent properties. The product is particularly suitable for application on **STUCCO DI VENEZIA** and **MARMO DI VENEZIA**.

IMPORTANT NOTES:

- Before application, ensure that the surface is perfectly dry and hardened, and that it has good adherence to the supporting ground. It must be clean and free from oil, grease, mould, fungus, bacteria, efflorescence, or any other defect that could impair adherence or successful results.
- Protect containers from freezing (minimum + 5° C).
- Store in a cool, dry place and do not expose to direct sunlight.
- Use product at a temperature of the work environment and treated surface between 8°C and 35°C. Relative humidity must not exceed 75%.
- Do not allow drying to take place with temperature of the work environment and treated surface below +5°C.

TECHNICAL DATA:

Coverage	12-35 m ² /l = 0.030-0.080 l/m ² according to absorption of the substrate.
Storage	minimum 1 year in sealed packs at temperature higher than 5°C
Packages	1 l

Product not intended for uses provided for by Dir. 2004/42/CE on VOC emissions limits

The above information has been obtained from scrupulously controlled tests, and represents our best and most recent knowledge. This information is provided for reference purposes only. It is not binding upon the manufacturer, and neither may it constitute grounds for any kind of complaint whatsoever associated with the use of the products described, also considering that the conditions of use are beyond our control.

Please refer to the relevant Safety Data Sheet.